

SELO SAKTI

Selo Sakti adalah perusahaan yang bergerak dibidang usaha kontruksi, Perdagangan Umum dan Industry. Secara khusus lingkup usaha kami adalah manufaktur **Asphalt Mixing Plant (AMP)** merk **SELO SAKTI**. Berdiri sejak tahun 1991 yang terletak di daerah Bekasi -Jawa Barat.

Didukung workshop dan peralatan yang lengkap, kami menghasilkan produk yang mengutamakan kualitas dan mutu. Dengan tenaga kerja yang handal,berpengalaman dan berkompeten dibidangnya, menjadikan produk dan jasa kami menjadi yang terbaik.

Banyak customer kami yang merasa puas, baik dari segi produk maupun pelayanan purna jual kami. Mereka memberikan suatu kepercayaan kepada kami, karena kami memberikan solusi yang lebih baik.



JL.RAYA NAROGONG KM 12,5
PANGKALAN 3 CIKIWUL, BANTAR
GEBANG – BEKASI

TELP. (021)8250401,8250395
FAX. (021)8250395
SALES SERVICE . 08176647489 (HERI)



www.selosakti.com

Keunggulan Kami

MUDAH PENGOPERASIAN

Asphalt Mixing Plant SELO SAKTI mempunyai 2 sistem control pada panel kontrolnya, yaitu Full otomatis (FA) dan Semi otomatis (SA) dimana operator bebas menentukan system mana yang akan digunakan.

System FA telah menggunakan system komputerisasi, dimana untuk pengaturan JMF, pengaturan timer, pengaturan produksi dilakukan melalui input kedalam komputer. Mudah digunakan karena BERBAHASA INDONESIA.

Pada system SA penimbangan dilakukan secara manual dan proses mixing tetap dilakukan secara otomatis.

Sistem elektrik pada FA dan SA terpisah, sehingga jika terjadi masalah pada salah satu system maka system yang lain dapat digunakan.

SISTEM DAN KUALITAS YANG BAIK

Mixer unit menggunakan system **twin shaft pugmill** sehingga dapat dipastikan bahwa kualitas dari hasil pencampuran bisa terjadi secara merata dan dalam waktu singkat.

Paddle Tips dan Liners terbuat dari bahan hard metal dan anti abrasive steel sehingga dapat dipastikan keawetan dan daya tahannya. Design konstruksi yang baik memudahkan untuk perawatan dan perbaikan ,sehingga dapat menghemat waktu dan biaya bagi pelanggan.



KENYAMANAN SERVICE PURNA JUAL

Pelayanan service purna jual kami memberikan kenyamanan dan kepastian akan setiap produk yang kami tawarkan, baik untuk sparepart ataupun teknisi service. Dengan teknisi yang handal dan selalu mengutamakan mutu produk, telah banyak customer kami yang merasa puas memakai produk kami.



TECHNICAL SPESIFICATION
MODEL : SSAP 1000 SAV
CAPACITY: 60 T/H

1. COLD BIN	
Capacity	: 5M ³ Each Bin
Quantity	: 4 Sets
Driving Motor	: 0.2 Kw X 4p
2. CONVEYOR BIN 1	
Capacity	: 30 t/h
Dimension	: 500 mm Width X 1,25 Meters
Driving Motor	: 0.75 Kw X 4p X 1/20 GM
3. COLLECTING CONVEYOR	
Capacity	: 80 t/h
Dimension	: 500 mm Width X 2p X 12 Mtr Length
Driving Motor	: 1.5 Kw X 4p X 1/20 GM
4. JOINT CONVEYOR	
Capacity	: 80 t/h
Dimension	: 500 mm Width x 6 Meters Length
Driving Motor	: 1.5 Kw x 4p x 1/20

5. DRYER UNIT	
Capacity	: 80 t/h, at 4% aggregate moisture
Dimension	: 1,550 mm Diameter x 6,000 mm length
Driving Motor	: 11 Kw x 4p and Gear Reducer x 2

6. DRYER BURNER	
Burner	: Diesel fuel
Blower Burner	: High Pressure Blower
Driving Motor	: 15 Kw - 2 Pole

7. DRY TYPE DUST COLLECTOR	
a. CYCLONE	
Type	: Dry Type Single Cyclone, the dust is sent back to the bottom of hot elevator, and collected in order to minimize dust nuisance around the batch tower housing.
Quantity	: 1 set
b. EXHAUST FAN	
Type	: Centrifugal Plate Fan
Capacity	: Dry Cyclone 560 m ³ / min at 150 mmAq
Driving Motor	: Dry Cyclone 30 Kw x 4p

8. HOT ELEVATOR	
Type	: Bucket elevator,Pintle Chain Type
Capacity	: 80 t/h
Driving Motor	: 5.5 Kw x 4p x 1/20 GM

9.	VIBRATING SCREEN
Type	: 3.5 Deck, inclined type vibrating screen 4 Kinds Fraction of Aggregate
Capacity	: 80 t/h
Driving Motor	: 5.5 Kw x 4p
10.	HOT BIN
Type	: 4 Compartment type with discharge gates, solenoide valve and air cylinder
Total Volume	: 5 m ³
11.	WEIGHING SYSTEM
	a. AGGREGATE SCALE
Type	: Weighing indicator for load cell type measuring system
Dial Range	: 0 - 1,000 Kgs
	b. ASPHALT SCALE
Type	: Weighing indicator for load cell type measuring system
Dial Range	: 0 - 100 Kgs
	c. FILLER SCALE
Type	: Weighing indicator for load cell type measuring system
Dial Range	: 0 - 100 Kgs
12.	MIXER UNIT
	a. MIXER
Type	: Twin Shaft Pugmil Mixer

Capacity	: 1,000 Kgs / Batch
Driving Motor	: 30 Kw x 4p x 1/20 GM
b. ASPHALT SPRAY PUMP	
Type	: Gear Pump
Capacity	: 250 liters / minute
Driving Motor	: 5.5 Kw x 6p
c. HEATER FOR SPRAY PUMP AND SPRAY PIPING HEATER	
Type	: Electric heater for asphalt pump, spray pipe
Capacity	: 6 Kw

13. FILLER FEEDING EQUIPMENT	
a. FILLER ELEVATOR	
Type	: Bucket elevator,Pintle Chain Type
Capacity	: 8 t/h
Driving Motor	: 1.5 Kw X 4p X 1/20 GM
b. FILLER FEEDER	
Type	: Screw Feeder
Capacity	: 12 t/h
Driving Motor	: 0.75 Kw X 4p X 1/20 GM

14. Full Automatic & Semi Automatic Batch Control System
The gate is opened by air cylinder, equipped with mixing timer and operation solenoide valve for cylinders.

15. Switch Board
All directly switching system with swing switch

16. Air Compressor
Type : Air cooled, pressure switch control type
Driving Motor : 5.5 HP X 4p

17. OPERATION ROOM
The operation room is made of steel plate and is built separate from the main body in order to prevent vibration. The glass window is functions are assembled in this cabin.

18. WET CYCLONE (Optional)
Type : Wet Cyclone
Quantity : 1 Set

2-1 ASPHALT SUPPLY UNIT

1. ASPHALT KETTLE
Type : Direct heating type with flame tube
Capacity : 20,000 Liters
Quantity : 2 Sets

2. ASPHALT TRANSFER PUMP AND PIPING
a. ASPHALT PUMP
Type : Gear Pump
Capacity : 250 Liters /minute

Driving Motor	: 5.5 Kw X 6p
b. ASPHALT PIPING	
2inch bore piping materials with necessary valves	

3. BURNER	
Type	: Low Pressure Burner
Fuel Consumption	: 25 Liters
Quantity	: 2 Sets

2-2 FUEL OIL SUPPLY UNIT

1. FUEL OIL TANK	
Type	: Cylindrical and vertical Type
Capacity	: 10,000 Liters

2. FUEL OIL PIPING	
1.5inch bore piping materials from fuel oil tank to dryer burner and kettle burner , total length 15 meters.	

2-3 ELECTRIC WIRING

All SV cable materials from switch board to each motor

*** Spesifikasi dapat berubah sewaktu-waktu demi peningkatan mutu tanpa pemberitahuan terlebih dahulu**